

FORMA 2700 THREE-SIDED

WITH FLA3+ 2490 AUTOMATIC ETHANOL BURNER

Net Zero fireplace with the BEV Technology®  BEST BUILD QUALITY

THREE-SIDED FIREPLACE

The three-sided fireplace brings a true panoramic fire. Enjoy the widest flame from three different sides.


PROTECTIVE DEFLECTOR

With the attached deflector you can cover the fireplace housing with combustible materials.

The product passed extensive tests carried out by the leading certification institutes. It is manufactured according to UL standards and is O-TL certified, meeting the most demanding safety and quality requirements.

TRUE ZERO CLEARANCE

The feature that allows you install the fireplace in a housing construction made of combustible materials.



INTEGRATED CONTROL PANEL

The FLA3+ burner has an intuitive control panel and an inlet for automatic refuelling.

AUTOMATIC FLA3+ BURNER

The automatic burner with the patented BEV Technology® is the most advanced product in the industry ensuring the cleanest burning process without any smoke, smell or ash. The flame is produced by combusting ethanol vapors and has no direct contact with the liquid fuel.

REMOTE CONTROL

Control the fire with the included remote, app on your smartphone or home automation system.

TECHNICAL GLASS PANEL

The dedicated toughened glass plate covers the flame making it stable and even.

Forma 2700 Three-Sided

Burner model	FLA3+ 2490 (BEV Technology®)
Fuel tank capacity	45.9 L
Maximum burn time	36 hours
Maximum heat output	22.5 kW
Minimum room cubature	225 m ³
Flame height regulation	6 stages
Weight	221.9 kg
Fuel type	bioethanol 95 - 96,6%
Flue	not required
Air change rate	1 space volume per hour
Power supply	230 V
Finish	black powder coating
Materials	steel, galvanized steel, toughened glass
Application	for indoor use only

CONTROL OPTIONS



included




included



optional

'FLA3 NET-ZERO' APP

Control the fire with your smartphone!



optional tray with 5 ceramic logs or white stones
(installed on the top of the burner, behind the fire line)

O-TL certified 

Manufactured to UL standards

